

ELECTRICAL SPECIFICATION

Nominal Diameter	166mm/ 6.54 inch
Frame	Iron
Magnet	Ferrite Ring
Magnet Diameter	100mm
Nominal Impedance	8 Ohm
Magnetic Gap Depth	4mm
Power RMS	120W
Sensitivity 1W/ 1M	91db
Frequency Range	75- 5.5kHz
Voice Coil Diameter	35.5mm/ 1.3 inch
Winding Material	Copper
Former Material	Aluminium
Winding Depth	11mm
Surround (Damper)	Cotton
Cone and Dust Cap	Paper
Surround Material	Polycotton
Surround Design	Triple-roll

THIELE & SMALL PARAMETERS

Rosonanco Frequency	Fs	75hz
DC Resistance	Re	6 Ω
Mechanical Factor	Qms	2.364
Electrical Factor	Qes	0.906
Total Factor	Qts	0.655
BL Factor	BL	5T.m
Effective Moving Mass	Mms	9gr
Compliance	Cms	464 μ M/N
Equivalent Cas Air Load	Vas	18L
Effective Piston Area	Sd	16m ²
η (Eta Zero)	η_0	0.80%

MOUNTING & SHIPPING INFORMATION

Overall Diameter	166mm
Bolt Circle Diameter	158mm
Baffle Cutout Diameter	144mm
Depth	80mm
Net Weight	1.2kg

